

AQUAPRO 8210 2K UltiMatte Water Based Floor Finish

AQUAPRO 8210 is a high performance, two pack, water based, low gloss floor finish that has exceptional abrasion and chemical resistance and is ideal for commercial and high traffic environments where a low gloss, “raw uncoated” finish look is required.

Advantages

- Easy to apply
- Very low gloss, uncoated finish look
- Excellent abrasion resistance
- Excellent chemical resistance
- Fast drying
- Low VOC

Typical Applications

Interior use only. Timber, particleboard & cork flooring.

*Not suitable for exterior or wet area applications e.g. bathrooms or around swimming pools.
Caution: floor will be slippery when wet.*

Coverage

Approximately 12 - 15m² per litre.

Coverage is dependent upon the porosity of the substrate (timber) and the equipment used to apply the coating.

Application Method

By roller cover or water based applicator and a high quality brush.

- Roller or Applicator 10mm nap roller.
- Brush

Thinning

Not normally required. 5-10% AQUAPRO 4300 Wet Edge Extender may be added in particularly hot environments where a high ambient room temperature can be expected. Stir whilst adding.

Mixing Ratio

10A:1B Add 1 part AQUAPRO 8770 Part B Hardener to 10 parts AQUAPRO 8210 Part A by volume.

AQUAPRO 8210 UltiMatte

2k water based floor finish.



Pot Life

3 hours at 20°C. High temperatures will shorten pot life.

Dry Time

Recoat:	3-4 hours
Walk in socks:	4-6 hours
Light Traffic:	After 24 hours

- Low temperatures, cold damp conditions and heavy film thickness will retard drying times.
 - Direct sunlight and draft during drying may affect the final gloss level of the coating.
-

Application

Preparing the floor to a professional standard is essential to achieve the best results.

To ensure the most uniform finish on timbers such as Radiata, Cypress and Kauri pine, Polycure recommends the use of FASTASEAL 3030 Clear Sealer as the first coat on raw timber. For further information, contact Polycure Technical.

Preparation:

- Fill all nail holes with a water based putty, allow to dry.
- Sand uncoated floor with 150-180 grade sandpaper or screenback on a flexible pad to ensure floor is uniformly dull with no sanding scratches, nibs or fur. Vacuum thoroughly. Take care to avoid scratching the surface.
- **To achieve an uncoated raw appearance:** Apply a liberal first coat of AQUAPRO 8210 UltiMatte (as a Sealer coat) directly to the raw flooring using a 10mm nap roller cover and good quality brush to cut in around skirting boards and edges. Allow to dry per datasheet.
- **For Tannin Prone or Problem Timbers:** Polycure recommends the use of FASTASEAL 3535 to reduce the risk of tannin bleed. Note: The application of FASTASEAL 3535 as the first coat on raw timber will enhance the natural colour of the timber, providing a deeper rich colour to the floor.
- Thoroughly sand the coated floor with 180 grade sandpaper or screenback, remove all nibs, fluff and fur. Vacuum all dust. Take care to avoid scratching the surface.
- Apply a second coat of AQUAPRO 8210 2K UltiMATTE. Allow to dry for 3 to 4 hours.
- **Third coat:** Apply the final coat of AQUAPRO 8210 UltiMATTE. Polycure recommends to achieve maximum protection and life out of your coated floor that a standard 3 coat system is applied.

*Note: AQUAPRO 8210 UltiMatte 2K dries quickly, therefore it is important not to brush areas too far ahead of the roller or applicator bar at skirtings or edges so that a wet edge is maintained at all times, this will avoid a noticeable darker line in the finished floor around skirtings and floor edges. **Uneven application may cause different wetting of the timber and consequently a different colour in higher build areas.** Do not apply when temperature is less than 10°C or greater than 35°C.*

*Only pour sufficient coating to complete the job, replace the lid immediately as exposure to the environment can cause the product quality and performance to be affected. **Do not return unused product to the can as this will cause the remaining material to increase in viscosity.***

AQUAPRO 8210 UltiMatte

2k water based floor finish.



Properties	Colour	Clear
	Finish	Matt
	Build	Good
	Sandability	Good
	Solvent Resistance	Excellent
	Water Resistance	Excellent
	Levelling & Flow	Excellent
	Pack Sizes	5L
	Product Code	8210-0A
	Clean Up	Clean all equipment using water.
	Shelf Life	12 months, see label for use by date. Do not use product past use by date.

Refer to the AQUAPRO Product Information Guide for more information

Note: All coatings provide protection for the timber or substrate. However, no coating is indestructible and all coatings will mark or scratch depending upon what comes into contact with the coating. Sharp objects including sand and grit will scratch the surface of any coated floor regardless of coating type. In high traffic commercial environments such as hair dressing salons, night clubs and taverns many factors need to be considered when choosing a coating system. Refer to the Product Information Guides for further information.

Health & Safety

Before handling, refer to the Safety Data Sheet for health and safety information. Ensure that all personnel using this product have read and understood this data sheet and the associated SDS and packaging label before using this product.

Note: Coatings give off strong solvents and odours during the drying process. People and pets should be removed from the building during the application and drying of coatings. All food and fabrics should also be removed to reduce the risk of them becoming tainted during the drying process.

ABN 40 000 041 136
21 Marigold Street, Revesby NSW 2212, Australia, P +61 2 9795 3700 F +61 2 9771 3601
sales@mirotone.com.au

www.polyure.com.au